



Material:

- **Bar** : Brass with Polished Chrome-Plated finish. Secure to post with a concealed screw.
- **Post** : Brass with Polished Chrome-Plated finish. Mount on the bracket by grub screw along with a bar.
- **Bracket** : Brass with a machined finish. Mount on the wall to hold the whole unit.
- **Flange Cover** : Brass with Polished Chrome-Plated finish. Mount on the wall bracket to conceal mounting screws

Installation:

- Select an appropriate location to install your product, Pierce wall with a drill.
- Insert the plastic sleeves into the drilled cavity. Then mount the bracket on the wall with the help of a screw set provided with plastic sleeves for proper attachment in the material.
- Join the bar and posts together with a concealed cheese head screw (M4 x 0.7). Attach stopper at the open end of the bar.
- Then mount the assembly of posts and bar on a wall bracket with the help of grub screws provided.
- After secure assembly on wall bracket unit is ready to use.

Specification:

- The hollow Towel bar (Brass) has a polished chrome-plated finish with an inner diameter of 16mm and an outer diameter of 18mm. Bar thickness is 19 Gauge (1mm).
- Bar secured to post with the help of cheese head screw (M4 x 0.7) provided.
- Post is in a cylindrical shape with an outer diameter of 18mm. Secure to the wall bracket with the help of a grub screw provided.
- Polished chrome-plated finish flange cover has an outer diameter of 60mm with a thickness of 21 Gauge (0.8mm).
- SS 304 machined finish screw provided with ABS plastic sleeves to secure wall bracket on the wall.
- Hex L-key of M4 screw size provided to secure unit on the wall bracket.