For Residential and Commercial Applications

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative

C8478 Series

Series

Swing Nozzle Assembly, Flanged Wall Mount

Sizes:

Swing Nozzle Assembly, Flanged Wall Mount with 6" to 10" Swing Nozzle

Features & Benefits:

- Swing Nozzle stream regulator outlet
- Made from high quality brass
- Perfect Combination Of Design And Function
- Suitable For Your Modern Kitchen
- Superior Corrosion & Rust-Resistant Finish
- Safe, Easy To Clean, Use And Install
- Warranty 3 Years

Product Compliance:

California Proposition 65

Performance Data:

Pressure: 20-125 PSI

Temperature: 40°F to 140°F

Aerators:

Lar

□0.

□1.

Standard Aerator	Suffix	
□0.20 GPM	E1	
□ 0.50 GPM	E2	
□1.00 GPM	E3	_
□1.50 GPM	E4	
□1.80 GPM	E5	_
□2.20 GPM	E6	_

ZU GPM	Eb	_ Vandal Resistant Laminar Flow Outlet	Suffix	
minas Flass		□ 0.35 GPM	H1	
minar Flow Outlet	Suffix	□ 0.50 GPM	H2	
.50 GPM	F1	□1.00 GPM	Н3	
.50 GPM	F2	□1.50 GPM	H4	

Vandal Resistant

Aerator

□ 0.35 GPM

□ 0.50 GPM

□1.00 GPM

□1.50 GPM


Suffix


G1

G2

G3

G4






Dimensions - Weights

MODEL	Main Body		DIMENSIONS				WEIGHT
	Wall Mount	Swing	Swing		Length B		
	Elbow	Nozzle	Leng	th A			
			in	mm	in	mm	lbs.
C8478	C8477.01	C8179	6"	152	1.73"	44	1.33
C8479	C8477.01	C8180	8"	203	2.48"	63	1.40
C8480	C8477.01	C8181	10"	254	3.24"	82	1.47

NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.





US & Canada :- +1-678 666 2001