



Rough Opening
5.31" wide x 5.11" high
(135 x 130mm)
3.34" (85mm) minimum
recessed depth

Material:

- **Shell and Flanges** : 18-8, Type-304, 22-gauge (0.8mm) stainless steel. One-piece, seamless construction with two countersunk mounting holes.
- **Support Posts** : Two Heavy-duty cast zamak support posts with chrome-polished finish.
- **Mounting Bracket** : Plated steel mounting clamp attaches to back of unit with two sheet-metal screws for installation in stud wall construction and countertop aprons.
- **Spindles** : Two Chrome-polished plastic spindles equipped with heavy-duty internal springs.
- **Hood** : 18-8 Type-304, 22-gauge (0.8mm) stainless steel. Hood hinged to shell.

Installation:

- For installation in stud wall construction and countertop aprons without backing, Loosely attach the mounting clamp to back of the unit with sheet-metal mounting screws.
- Insert the product into the rough opening. Adjust mounting clamp so it grips surface inside rough opening.
- Secure in place by tightening two sheet-metal mounting screws.

Note: For installation in stud wall construction and countertop aprons with backing: Discard mounting clamp furnished with the unit. Insert unit only into a rough opening and secure with sheet-metal screws furnished. Backing must comply with local building codes

Specification:

- Recessed toilet tissue dispenser shall be constructed of Type-304, 22-gauge (0.8mm) stainless steel with Chrome polished finish. Shell and flange shall be drawn, one-piece, seamless construction. The Spindle shall be equipped with a heavy-duty internal spring. Unit shall be furnished with plated steel mounting clamp for stud wall construction and countertop aprons.