
For Residential and Commercial Applications


Job Nam <u>e</u>	Contractor
Job Location	Approval
Enginee <u>r</u>	Contractor's P.O. <u>No.</u>
Approval	Representative

Series: Pre Rinse

Ecoline 8" Wall Mount, Pre-Rinse Unit w/ 1.15GPM Spray Valve

C9576







Features & Benefits:

- 44" flexible stainless steel hose w/ heat resistant handle and hold down ring
- 1.15GPM Spray Valve
- 18" rigid riser tube
- Ceramic hot & cold cartridges
- Adjustable wall bracket
- Lever handles with colorful coded screws
- Inlet 1/2" in NPT Female and has Adjustable Centers
- Material: Polished chrome plated brass body

Performance Data:

Pressure: 20 - 125 psi [1.38 - 8.62 bar] Temperature: 40 F - 140 F [4.44 C - 60 C] Flow rate: : 1.15 GPM [4.35 L/min] @ 60 psi

Aerators:

Standard Aerator	Suffix	Vandal Resistant	
□0.20 GPM	E1	Laminar Flow	Suffix
□ 0.50 GPM	E2	Outlet	
□1.00 GPM	E3	□0.35 GPM	H1
□1.50 GPM	E4	□ 0.50 GPM	H2
□1.80 GPM	E5	□1.00 GPM	Н3
□2.20 GPM	E6	□1.50 GPM	H4

Laminar Flow Outlet	Suffix	Vandal Resistant	
□0.50 GPM	F1	Aerator	Suffix
		□0.35 GPM	G1
□1.50 GPM	F2	□ 0.50 GPM	G2
		□ 1.00 GPM	G3

Optional Pre-Rinse Spray Valves:

	Spray Valve	Flow Rate
Ī	C9526	1.15GPM
	C8149	1.42GPM
Ī	C9520	1.42GPM
Ī	C8249	4.50GPM

Product compliance:

California proposition 65

Warranty: Four year (Limited)

NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all The information contained herein is not intended to replace the full of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.





